1: Warner E-5 (1926-1929) 1937
OI 17 Murngin OI 17

The technique has not been lost, for several old men know how they are made.

Food Grinding Stone.—These small stones are used to grind up seeds or nuts gathered by the women and to break mussel shells. They are three or four inches in length, the same in width, and about two inches in thickness. A rock of the proper shape is used and no artificial shaping is done. However, there is a socializing agency at work, in the sense that a round rock flattened on the two opposite sides is preferred and, further, the grinding gradually works the center into a cavity; such a stone has now assumed value and is sought for by a woman in preference to a new stone. The depression is sometimes an inch and a half deep. The stone weighs about a pound and a half normally, but varies from one-half to two and a quarter pounds.

A larger-sized grinding stone also used by the native women is five inches by three inches and weighs about four pounds. It is also flattened on two sides.

The upper grinding stone, or grinder, is usually egg-shaped and is nothing more than an untreated smooth water stone. It has a diameter of about one and one-half inches and weighs from one-eighth to a quarter of a pound.

Camp Wells.—Two types of wells are dug during the dry season. The first is made more or less unconsciously by each person's excavating a small amount of earth from the bottom of a shallow water hole and continuing this process as the water dries up in the latter part of the season. The second variety is purposefully dug where water is known to be. It may be one or two feet in diameter or large enough to allow a man to get down in it to fill his paper-bark basin. Wells of this type sometimes reach a depth of four or five feet. Associated with an artificially constructed well is usually found the long-handled paper-bark container, made by attaching a long stick to an ordinary container with fiber string.

Bridges.—The Murngin often construct rude bridges by placing one to three tree trunks over the smaller streams about the camp.

7. Articles Used in Ceremonies

Feather Headdresses.—The chief materials used in making feather headdresses are resin, beeswax, fiber string, feathers of various birds, leg bones of birds, and wooden or sting-ray prongs. The feathers are hafted to the wooden, bone, or sting-ray pins with ironwood resin. White and black cockatoo tail feathers, the crest of the sulphur-crested cockatoo, emu, jabiru, egret, heron, native companion, goose, and duck feathers are the chief ones used, but feathers of other birds are also utilized.

The pin of the Gunabibi type of headdress is four to six inches long, and usually incised and ruddled if of wood. Sometimes the pin is made from the leg bone of a bird. The resin or beeswax hafting is in the shape